



PIT VENT REQUIREMENT:  
 MUST BE ACCORDING TO NATIONAL ELECTRIC CODE.  
 PIT MUST BE VENTED TO SOME POINT OUTSIDE THE  
 BUILDING. CUSTOMER SUPPLIED FAN NEEDS TO BE  
 INSTALLED A MINIMUM OF 18" ABOVE FINISHED FLOOR.  
 A FAN (NOT SUPPLIED) SHOULD CONSTANTLY  
 REMOVE AIR FROM THE BOTTOM OF THE PIT  
 FLOOR AT A RATE OF SIX AIR CHANGES PER HOUR.

80 PSI CLEAN DRY AIR  
 WITH SHUT OFF AND  
 REGULATOR AND ENDING  
 WITH 1/2" PRESS-LOCK  
 TYPE FITTING FOR 1/2"  
 DIA. PLASTIC AIR LINE  
 (30 FEET SUPPLIED BY MD)

FUSIBLE DISCONNECT  
 230VAC, 3 PH, 60 HZ, 40 AMP.

TO CARBON  
 MONOXIDE  
 DETECTOR  
 POWER FEED (CONDUIT) FROM  
 DISCONNECT TO MD CONTROL  
 BOX SUPPLIED/INSTALLED  
 BY CUSTOMER  
 MUSTANG DYNAMOMETER  
 CONTROL BOX

ALL CONDUIT ENDS  
 REQUIRE SEAL TITE ENDS  
 (CUSTOMER SUPPLIED)

1'-6" (18") MIN  
 4"  
 1'-6" MIN

THE INFORMATION ON THIS DRAWING IS THE PROPERTY OF MUSTANG DYNAMOMETER, INC. AND IS TO BE USED ONLY FOR THE PROJECT AND SITE SPECIFICALLY IDENTIFIED HEREON. IT IS NOT TO BE REPRODUCED, COPIED, OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM. WITHOUT THE WRITTEN PERMISSION OF MUSTANG DYNAMOMETER, INC. THIS DRAWING IS NOT VALID FOR ANY OTHER PROJECT OR SITE. MUSTANG DYNAMOMETER, INC. RESERVES THE RIGHT TO MAKE CHANGES TO THIS DRAWING WITHOUT NOTICE.

REV: 20020401

**MD MUSTANG DYNAMOMETER**  
 2800 RIVINGTON AVE., TOWSON, MD 21286  
 TEL: (410) 286-4000 FAX: (410) 286-8810

DO NOT SCALE  
 THESE DIMENSIONS

DATE: 12/14/03  
 TIME: 1:24 PM

SCALE: 1:24 (N/A)

DATE: 12/14/03  
 TIME: 1:24 PM

SCALE: 1:24 (N/A)

DATE: 12/14/03  
 TIME: 1:24 PM

SCALE: 1:24 (N/A)

REV	BY	DATE
A	TEJ SNOVO3	
1	RELEASE	
REVISIONS		